Speed

Technical data PistenBully ParkPro


| Engine | |
|----------------------------|-------------------------|
| Туре | Cummins QSL 9 |
| No. of cylinders | 6 |
| Displacement | 8.9 l / 2.4 gal |
| | 8,900 ccm / 543 cu.in |
| Power output (ECE) | 272 kW / 370 hp |
| Exhaust emissions standard | Euro 3A, EPA TIER 3 |
| Max. torque | 1,519 Nm / 1,120 ft lbs |
| | at 1,500 rpm |
| Tank capacity | 260 l / 69 gal |
| Tank capacity | from 19 l/h / 5 gal |
| Drive pump | 140 ccm / 8.5 cu.in |
| | |
| | |
| Driving peformance | |


0 – 23 km/h / 0 – 14 mph continuously variable

| Electrics | | |
|----------------------|---------------------------|--|
| Low-voltage system | 24 V | |
| Alternator | 24 V/140 A | |
| Batteries | 2 x 12 V / 135 Ah | |
| Cold start rating | 900 A | |
| Lightning | | |
| Front | 2 H7 front-headlights and | |
| | 2 H11 working headlight | |
| Rear | 2 H11 rear-headlights | |
| Lateral | optional | |
| Search headlight | Twin searchlights | |
| Additional headlight | - | |

| ROPS certificate | yes |
|-----------------------------------|-----------------------------|
| Driver's seat | adjustable |
| Operating elements | display with display screen |
| Glass | Front, rear and side |
| | windows heated |
| Rear mirrors | heated |
| Wipers | cooling-water heated |
| | |
| Options | |
| Hydraulically foldable sideflaps | |
| Front high pressure connection | |
| Xenon set | |
| Solid tires | |
| Magnum sprocket | |
| Hydraulic oil pre-heating | |
| Trailer hitch | |
| Cableway emergency operation | |
| Foldable galery (not available fo | r all countries) |
| Rear camera | |
| Harness belt | |
| | |

Cabin





Dimensions

| Width | without tracks | 2,500 mm / 98.4" |
|--------------|--------------------------------------|--------------------|
| | over combined tracks / steel tracks | 4,206 mm / 165.6" |
| | over tiller with intermediate flaps | 5,500 mm / 216.5" |
| | over tiller and foldable sideflaps | 6,400 mm / 252" |
| Blade | width open | 5,560 mm / 218.9" |
| | width wide | 4,570 mm / 179.9" |
| | Height | 1,000 mm / 39.4" |
| Height | above everything | 2,830 mm / 111.4" |
| | when driver's cabin tilted | 3,250 mm / 128" |
| Ground clear | ance | 350 mm / 13.8" |
| Length | with blade and tiller | 9,010 mm / 354.7" |
| | with blade, tiller and track-setters | 10,310 mm / 405.9" |
| Load area | Length | 2,120 mm / 83.5" |
| | Width | 1,920 mm / 75.6" |
| Suggested | Length | 11,000 mm / 433" |
| garage | Width | 6,000 mm / 236" |
| dimensions | Height | 3,500 mm / 138" |

Weights

| _ | | |
|---------------------|-------------------|-------------|
| Tare weight | with combined | 7,340 kg / |
| | tracks | 16,182 lbs |
| | with steel tracks | 8,020 kg / |
| | | 17,681 lbs |
| Gross weight limit | | 11,800 kg / |
| | | 26,015 lbs |
| Payload on platform | | 1,500 kg / |
| | | 3,307 lbs |
| | | |